

SPECIFICATIONS(MINI OPEN FRAME SERIES)

* FEATURES:

- * High Brightness.
- * External OSD key board.
- * Fast response time.
- * Low electromagnetic wave and power saver.
- * RoHS compliance.

SPECIFICATIONS:

| | | |
|---------------------------------|-----------------------------------|--|
| Model | | MT32W-26763-1 |
| ModelSelectionGuide | | VGA+DVI |
| LCD Panel | Screen Size | 31.51 |
| | Pixel Pitch(mm) | 0.51075*0.51075 |
| | Backlight | LED |
| | Response | 6ms |
| | Aspect Ratio | 16:9 |
| Viewing Angle | Horizontal | 178° |
| | Vertical | 178° |
| Video | Input Mode | WXGA |
| | Horizontal | 31~48KHz |
| | Vertical | 59~60Hz |
| Display | Resolution | 1366*768 |
| | Contrast Ratio | 1200:1Typ |
| | Brightness | Min 240 cd/m2 |
| | | Typ 300 cd/m2 |
| | Horizontal Size | 697.6845 |
| | Vertical Size | 392.256 |
| | Colors | 16.7M |
| Bandwidth | 74.4MHz Typ. | |
| Power | Consumption | 54 W Typ. ± 20% |
| | Management | VESA-DPMS |
| | | 54W Typ. ± 20% |
| | | PowerDown |
| | | Mode</=9Watts |
| Input | AC Power(Input 100-240VAC) | |
| Operations | Function Key | 5Key |
| | OSD Adjustment | Constrast,Brightness,Phase,Clock,H-position,V-position,....Exit |
| Input Signal | | 0.7Vpp Analog75 ohm |
| Sync | | TTL Level Separate,Composite |
| Windows Compatibility | | Windows98/2000 |
| PC Interface | | Analog Interface |
| Signal Cable | | Standard VGA cable w/15-pin D-sub |
| EMI/Safety | | |
| Operating Temperature | | 0°C~50°C |
| Humidity | | 10~85% |
| Outer Dimension(L*W*H)mm | | 727.6x431.5x91.8 |

